



Trusted by Professionals Since 1989



EGF-6088W

ELID Wide Lane Flap Barrier

Smart turnstile (block gate) is a high-tech product which mainly provides intelligent management to passageway. It is a upgrade product of intelligent tripod turnstile and swing barrier. This product is finely processed with complete functions and high level, suitable for high-level neighborhoods, intelligent buildings, hotel, subway, port and club, etc.

This equipment is subtly integrated with machine, electronics, micro-processor control and ID identification, provides convenience for the use of card reader identification equipment, such as IC card, ID card, bar code and fingerprint. It can carry out intelligent control and management to the passageway through choosing various identification equipment and adopting fair, reliable security protection, alarming equipment and direction indicating equipment...

Classified into two kinds: single motor (suitable for single passageway and multiple passageway); Double motors (suitable for multiple passageways)


we make your world secure 🔑

Technical Parameters

- Housing material: 304# stainless steel
- Working voltage: AC220±10%V 50±10%HZ
- Drive motor: DC24V brush motor
- Size: 1200mm (L) * 300mm (W) * 1000mm (H)
- Retractable arm length: 250/425 mm
- Passage width: ≤550/ 900mm
- Direction: single or bi-directional (optional)
- Working environment: indoor/outdoor (with a roof) -10°C~70°C
- Relative humidity: ≤90% coagulation free
- Time of opening/closing: 0.6 second
- Pass speed: 40 persons/min (open), 25-30 persons/min (closed)
- Time to work after power on: 3 seconds
- Reset time after break down: 10 seconds
- Normal running life: >3 million
- Communication interface: standard RS485 interface, distance ≤1200m
- Input interface: +12V level signal or pulse width>100ms 12V pulse, drive current>10mA

Standard Functions & Features

- Alarm function : when arms are pushed by force illegally, alarm will be triggered automatically and arms will be set locked. turnstile can check by itself when it is have problem, it is good for customer to maintain and use
- Turnstile can setting the working condition by press the button of main control board.
- This model is newest second generation of movement (mute), soft baffle (PU mold)
- Anti-pinch function: turnstile have Mechanical/ infrared induction Anti-pinch functions(when it is meet the hinder during the reset time, the electrical machine closed work automatically in specified time, the turnstile will default the delayed and reset again till reset succeed)
- The turnstile will closed the door when somebody enter the gate illegal, Tailgating or break into negative direction gate.
- Before received the open signal, the turnstile will lock automatically
- Automatic Reset Functions: after you swap the card, during the specific time (the system is 10s), if you didn't pass the turnstile, the system will cancel your authority automatically to pass the gate, (reset time is 1~60s you can adjust it what time is suit for you). totally meet the fire protection needs
- Infrared reset function & Infrared induction clamp function (3 pairs Infrared)



For more information: Check out the website at www.elid.com, or contact our dealers. ELID has a policy of continuous research and development, and reserves the right to change specifications without notice.

www.elid.com